


# 70X70X10mm


## General Specifications

| | |
|---|---|
| Airflow | 14.9~31.0 CFM |
| Static Pressure | 2.3~4.8 mm-H2O |
| Housing | Plastic Material UL 94V-0 P.B.T. |
| Blade | Plastic Material UL 94V-0 P.B.T. |
| Lead Wire | UL1007 #26 AWG |

## Dimensions:mm




## Performace




## Specifications

| Model NO. | Bearing | Rated Voltage | Operating Voltage Range | Speed | Airflow | Static Pressure | Current | Power | Life at 40°C L10 | P-Q Curve | Noise | Weight |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | VDC | VDC | RPM | CFM | mm-H2O | mA | W | HOUR | | dBA | g |
| GD057010LB-H | 2BALL | 5 | 4~5.5 | 2300 | 14.9 | 2.3 | 160 | 0.80 | 80000 | 6 | 20.5 | 35 |
| GD057010MB-H | 2BALL | 5 | 4~5.5 | 2700 | 17.5 | 2.7 | 200 | 1.00 | 80000 | 5 | 24.0 | 35 |
| GD057010HB-H | 2BALL | 5 | 4~5.5 | 3100 | 20.1 | 3.1 | 270 | 1.35 | 75000 | 4 | 27.0 | 35 |
| GD127010LB-H | 2BALL | 12 | 7~13.2 | 3700 | 23.9 | 3.7 | 130 | 1.56 | 80000 | 3 | 31.0 | 35 |
| GD127010MB-H | 2BALL | 12 | 7~13.2 | 4300 | 27.8 | 4.3 | 170 | 2.04 | 80000 | 2 | 34.5 | 35 |
| GD127010HB-H | 2BALL | 12 | 7~13.2 | 4800 | 31.0 | 4.8 | 250 | 3.00 | 75000 | 1 | 37.0 | 35 |



www.gulf.com.tw TEL:+886-7-5219966 E-MAIL:service@gulf.com.tw