



Specifications

Model NO.	Bearing	Rated Voltage	Operating Voltage Range	Speed	Airflow	Static Pressure	Current	Power	Life at 40°C L10	P-Q Curve	Noise	Weight
GD128038LB-P	2BALL	12	7~13.2	3400	47.6	7.5	240	2.88	80000	6	41.5	172.6
GD128038MB-P	2BALL	12	7~13.2	4200	58.9	11.2	380	4.56	80000	5	47.0	172.6
GD128038HB-P	2BALL	12	7~13.2	4900	69.2	15.2	580	6.96	75000	4	51.5	172.6
GD128038EB-P	2BALL	12	7~13.2	5700	81.2	20.5	800	9.60	65000	3	55.0	172.6
GD128038UB-P	2BALL	12	7~13.2	8000	116.0	37.2	2000	24.0	65000	2	62.5	172.6
GD128038SB-P	2BALL	12	7~13.2	9000	132.9	45.3	2700	32.4	60000	1	65.0	172.6
GD248038LB-P	2BALL	24	12~26.4	3400	47.6	7.5	130	3.12	80000	6	41.5	172.6
GD248038MB-P	2BALL	24	12~26.4	4200	58.9	11.2	200	4.80	80000	5	47.0	172.6
GD248038HB-P	2BALL	24	12~26.4	4900	69.2	15.2	280	6.72	75000	4	51.5	172.6
GD248038EB-P	2BALL	24	12~26.4	5700	81.2	20.5	420	10.08	65000	3	55.0	172.6
GD488038LB-P	2BALL	48	24~56.0	3400	47.6	7.5	80	3.84	80000	6	41.5	172.6
GD488038MB-P	2BALL	48	24~56.0	4200	58.9	11.2	110	5.28	80000	5	47.0	172.6
GD488038HB-P	2BALL	48	24~56.0	4900	69.2	15.2	150	7.20	75000	4	51.5	172.6
GD488038EB-P	2BALL	48	24~56.0	5700	81.2	20.5	200	9.60	65000	3	55.0	172.6