



Specifications

Model NO.	Bearing	Rated Voltage	Operating Voltage Range	Speed	Airflow	Static Pressure	Current	Power	Life at 40°C L10	P-Q Curve	Noise	Weight
GD128038LB-S	2BALL	12	7~13.2	6000	77.2	18.6	530	6.36	60000	5	48.4	185.5
GD128038MB-S	2BALL	12	7~13.2	7000	89.8	25.2	750	9.00	60000	4	53.3	185.5
GD128038HB-S	2BALL	12	7~13.2	8500	109.1	34.2	1250	15.00	60000	3	58.8	185.5
GD128038EB-S	2BALL	12	7~13.2	10000	127.6	46.8	1900	22.80	60000	2	62.8	185.5
GD128038SB-S	2BALL	12	7~13.2	12000	153.8	62.6	3100	37.20	60000	1	68.1	185.5
GD248038LB-S	2BALL	24	12~26.4	6000	77.2	18.6	340	8.16	60000	5	48.4	185.5
GD248038MB-S	2BALL	24	12~26.4	7000	89.8	25.2	400	9.60	60000	4	53.3	185.5
GD248038HB-S	2BALL	24	12~26.4	8500	109.1	34.2	620	14.88	60000	3	58.8	185.5
GD248038EB-S	2BALL	24	12~26.4	10000	127.6	46.8	1000	24.00	60000	2	62.8	185.5
GD248038SB-S	2BALL	24	12~26.4	12000	153.8	62.6	1550	37.20	60000	1	68.1	185.5
GD488038LB-S	2BALL	48	24~56.0	6000	77.2	18.6	200	9.60	60000	5	48.4	185.5
GD488038MB-S	2BALL	48	24~56.0	7000	89.8	25.2	240	11.52	60000	4	53.3	185.5
GD488038HB-S	2BALL	48	24~56.0	8500	109.1	34.2	310	14.88	60000	3	58.8	185.5
GD488038EB-S	2BALL	48	24~56.0	10000	127.6	46.8	440	21.12	60000	2	62.8	185.5
GD488038SB-S	2BALL	48	24~56.0	12000	143.36	62.6	800	38.40	60000	1	68.1	185.5