



Specifications

Model NO.	Bearing	Rated Voltage	Operating Voltage Range	Speed	Airflow	Static Pressure	Current	Power	Life at 40°C L10	P-Q Curve	Noise	Weight
GD129238LB-S	2BALL	12	7~13.2	5000	97.1	15.2	450	5.40	60000	5	50.9	201.5
GD129238MB-S	2BALL	12	7~13.2	6000	118.0	23.4	750	9.00	60000	4	54.3	201.5
GD129238HB-S	2BALL	12	7~13.2	7000	132.2	28.1	1150	13.80	60000	3	57.5	201.5
GD129238EB-S	2BALL	12	7~13.2	8500	162.3	38.2	1900	22.80	60000	2	61.7	201.5
GD129238EB-S	2BALL	12	7~13.2	10000	196.5	52.4	3200	38.40	60000	1	66.3	201.5
GD249238LB-S	2BALL	24	12~28.0	5000	97.1	15.2	260	6.24	60000	5	50.9	201.5
GD249238MB-S	2BALL	24	12~28.0	6000	118.0	23.4	380	9.12	60000	4	54.3	201.5
GD249238HB-S	2BALL	24	12~28.0	7000	132.2	28.1	580	13.92	60000	3	57.5	201.5
GD249238EB-S	2BALL	24	12~28.0	8500	162.3	38.2	1000	24.00	60000	2	61.7	201.5
GD249238EB-S	2BALL	24	12~28.0	10000	196.5	52.4	1600	38.40	60000	1	66.3	201.5
GD489238LB-S	2BALL	48	36~56.0	5000	97.1	15.2	150	7.20	60000	5	50.9	201.5
GD489238MB-S	2BALL	48	36~56.0	6000	118.0	23.4	200	9.60	60000	4	54.3	201.5
GD489238HB-S	2BALL	48	36~56.0	7000	132.2	28.1	290	13.92	60000	3	57.5	201.5
GD489238EB-S	2BALL	48	36~56.0	8500	162.3	38.2	500	24.00	60000	2	61.7	201.5
GD489238EB-S	2BALL	48	36~56.0	10000	196.5	52.4	800	38.40	60000	1	66.3	201.5