



Specifications

Model NO.	Bearing	Rated Voltage	Operating Voltage Range	Speed	Airflow	Static Pressure	Current	Power	Life at 40°C L10	P-Q Curve	Noise	Weight
GD129238LB-P	2BALL	12	7~13.2	3300	80.5	7.8	450	5.40	80000	5	48.0	198.4
GD129238MB-P	2BALL	12	7~13.2	3800	92.6	10.9	640	7.68	80000	4	51.0	198.4
GD129238HB-P	2BALL	12	7~13.2	4300	103.8	13.1	950	11.40	75000	3	55.0	198.4
GD129238EB-P	2BALL	12	7~13.2	4900	117.3	15.5	1700	20.40	65000	2	57.0	198.4
GD129238EB-P	2BALL	12	7~13.2	7000	168.0	33.1	2800	33.60	65000	1	65.0	198.4
GD249238LB-P	2BALL	24	12~26.4	3300	80.5	7.8	250	6.00	80000	5	48.0	198.4
GD249238MB-P	2BALL	24	12~26.4	3800	92.6	10.9	350	8.40	80000	4	51.0	198.4
GD249238HB-P	2BALL	24	12~26.4	4300	103.8	13.1	470	11.28	75000	3	55.0	198.4
GD249238EB-P	2BALL	24	12~26.4	4900	117.3	15.5	600	14.40	65000	2	57.0	198.4
GD489238LB-P	2BALL	48	24~56.0	3300	80.5	7.8	130	6.24	80000	5	48.0	198.4
GD489238MB-P	2BALL	48	24~56.0	3800	92.6	10.9	170	8.16	80000	4	51.0	198.4
GD489238HB-P	2BALL	48	24~56.0	4300	103.8	13.1	290	13.92	7500	3	55.0	198.4
GD489238EB-P	2BALL	48	24~56.0	4900	117.3	15.5	290	13.92	65000	2	57.0	198.4