



Specifications

Model NO.	Bearing	Rated Voltage	Operating Voltage Range	Speed	Airflow	Static Pressure	Current	Power	Life at 40°C L10	P-Q Curve	Noise	Weight
GD121238LB-P	2BALL	12	7~13.2	4000	194.4	31.1	1900	22.80	80000	5	64.0	400
GD121238MB-P	2BALL	12	7~13.2	4400	213.7	34.2	2300	27.60	80000	4	66.0	400
GD121238HB-P	2BALL	12	7~13.2	5100	247.6	39.6	3100	37.20	65000	3	69.5	400
GD241238LB-P	2BALL	24	15~30.0	4000	194.4	31.1	850	20.40	80000	5	64.0	400
GD241238MB-P	2BALL	24	15~30.0	4400	213.7	34.2	1000	24.00	80000	4	66.0	400
GD241238HB-P	2BALL	24	15~30.0	5100	247.6	39.6	1600	38.40	65000	3	69.5	400
GD241238EB-P	2BALL	24	15~30.0	5800	281.5	45.1	2400	57.60	65000	2	72.5	400
GD241238EB-P	2BALL	24	15~30.0	6500	315.3	50.7	3200	76.80	65000	1	75.0	400
GD481238LB-P	2BALL	48	35~72.0	4000	194.4	31.1	460	22.08	80000	5	64.0	400
GD481238MB-P	2BALL	48	35~72.0	4400	213.7	34.2	550	26.40	80000	4	66.0	400
GD481238HB-P	2BALL	48	35~72.0	5100	247.6	39.6	750	36.00	75000	3	69.5	400
GD481238EB-P	2BALL	48	35~72.0	5800	281.5	45.1	1100	52.80	65000	2	72.5	400
GD481238EB-P	2BALL	48	35~72.0	6500	315.3	50.5	1550	74.40	65000	1	74.5	400