


120X120X25mm


General Specifications

Airflow	56.5~181.0 CFM
Static Pressure	3.1~24.3 mm-H2O
Blade	Plastic Material UL 94V-0 P.B.T.
Frame	Plastic Material UL 94V-0 P.B.T.
Lead Wire	UL1007 #22 AWG

Dimensions:mm



Performace



Specifications

Model NO.	Bearing	Rated Voltage	Operating Voltage Range	Speed	Airflow	Static Pressure	Current	Power	Life at 40°C L10	P-Q Curve	Noise	Weight
		VDC	VDC	RPM	CFM	mm-H2O	mA	W	HOUR		dBA	g
GD121225LB-Q	2BALL	12	7~13.2	2000	56.5	3.1	130	1.56	80000	4	29.3	205
GD121225MB-Q	2BALL	12	7~13.2	2800	81.8	6.0	220	2.64	80000	3	39.1	205
GD121225HB-Q	2BALL	12	7~13.2	4400	127.9	14.1	550	6.60	75000	2	51.4	205
GD121225EB-Q	2BALL	12	7~13.2	6000	181.0	24.3	1300	15.60	65000	1	60.5	205
GD241225LB-Q	2BALL	24	12~26.4	2000	56.5	3.1	85	2.04	80000	4	29.3	205
GD241225MB-Q	2BALL	24	12~26.4	2800	81.8	6.0	130	3.12	80000	3	39.1	205
GD241225HB-Q	2BALL	24	12~26.4	4400	127.9	14.1	320	7.68	75000	2	51.4	205
GD241225EB-Q	2BALL	24	12~26.4	6000	181.0	24.3	700	16.8	65000	1	60.5	205
GD481225LB-Q	2BALL	48	24~56.0	2000	56.5	3.1	60	2.88	80000	4	29.3	205
GD481225MB-Q	2BALL	48	24~56.0	2800	81.8	6.0	85	4.08	80000	3	39.1	205
GD481225HB-Q	2BALL	48	24~56.0	4400	127.9	14.1	180	8.64	75000	2	51.4	205
GD481225EB-Q	2BALL	48	24~56.0	6000	181.0	24.3	400	19.20	65000	1	60.5	205

www.gulf.com.tw TEL:+886-7-5219966 E-MAIL:service@gulf.com.tw